



## 800.572.9029 STEPSTONEPRECAST.COM







## **SHORT FORM SPECIFICATION**

SIZES:

S: CLASSIC

14" X 24" X 2 ½"

INSIDE AND OUTSIDE CORNERS

INSIDE RADIUS: 1, 2, 3, 4, 6, 8'

OUTSIDE RADIUS: 2, 3, 4, 6, 8'

1" RADIUS BULLNOSE WITH ¼" TOP

AND BOTTOM REVEAL

<u>MODERN</u> 18" X 18" X 2" 18" X 24" X 2" AIGHTS AND OUTSIDE C

STRAIGHTS AND OUTSIDE CORNERS 1"RADIUS BULLNOSE

RISER BLOCK 3" X 4" X 24" RISER TILE 6" X 12" X 1" SQUARE MODULAR
12" X 24" X 2 ½"
16" X 24" X 2 ½"
16" X 36" X 2 ½"
16" X 16" X 2 ½"
16" OUTSIDE CORNERS
OUTSIDE RADIUS: 2', 4', 6', 8'

ALL SIZES ARE NOMINAL

MATERIAL: 4,000 PSI HARDROCK CONCRETE, TYPE III CEMENT

FINISH: STIPPLED OR SANDBLAST

COLOR CHOICE: USING ACTUAL SAMPLES IS STRONGLY RECOMMENDED

DETAILS: VISIT STEPSTONEPRECAST.COM FOR DRAWINGS, DIMENSIONS AND RADIUS FINDER



PLEASE NOTE: ALL OF OUR PRODUCTS ARE MADE BY HAND FROM NATURAL MATERIALS. VARIATIONS IN COLOR ARE TO BE EXPECTED. TO CONFIRM COLOR, PLEASE REFER TO ACTUAL CONCRETE SAMPLES BEFORE PLACING ORDER. SOME MINOR CHIPPING MAY RESULT FROM SHIPPING, BUT IS NOT DETRIMENTAL TO APPEARANCE OR FUNCTION. STEPSTONE, LLC RECOMMENDS SEALING TO AID IN GROUT REMOVAL AND CLEANING PRIOR TO INSTALLATION. GROUT NATURALLY WILL BOND WITH CONCRETE. IMMEDIATELY REMOVE ANY GROUT SLURRY THAT COMES IN CONTACT WITH THE FINISHED FACE OF THE PRECAST CONCRETE PIECES. ALL SIZES ARE NOMINAL. SEE DETAILS FOR FURTHER INFORMATION. AVAILABLE IN OTHER STANDARD COLORS. SEE ACTUAL COLOR CONCRETE SAMPLES BEFORE ORDERING. THIS MATERIAL IS COPYRIGHTED AND IS INTENDED SOLELY FOR THE USE OF CUSTOMERS OF STEPSTONE, LLC